

Door Contact

Guarding you against unauthorised door and window openings and closures



Our **Door Contact** is designed to detect the opening and closure of doors or windows. Powered by a CR2 3V Lithium battery, it's particularly created to enhance operational efficiency, lower power consumption and reduce maintenance costs. Compact and slim in design, it's easy to install and blends naturally with any home decor.

The Door Contact alerts the LifeGuard unit of any irregular activities and sends low battery signals as well as regular supervision signals to check system integrity.

Super speed signal transmission and extensive communication range of up to 100 meters in open space. Designed to effectively reduce signal collisions and further extend battery life.

Features

- Long battery life
- Super speed signal transmission
- Powered by pre-inserted Lithium battery for easy installation
- Mounted on door or window frames
- Tamper protection to prevent unauthorised removal, sabotage or unsteady installation

- Randomised supervision signals to check system integrity and troubleshooting
- Low battery detection
- Power magnet allows for an overall side-to-side gap distance of 30mm space between the door contact and the magnets
- LED serving as a fault and test mode indicator
- Compliant with CE requirement

Specifications

- Battery: CR2 3V 850mAh Lithium battery x 1 (pre-inserted)
- Battery Life: 3-4 years (433MHz)
- Operating Temperature: =10°C to +50°C
- Operating Humidity: Up to 85% non-condensing
- Dimensions: 113mm x 27mm x 24.7mm

Specifications subject to change at discretion of INS LifeGuard.