

# Flashing Strobe Light

## Smoke Alarm Warning Device for the Hearing Impaired



### Key Features

- Hearing impaired warning device
- Interconnects to Brooks 240V smoke alarm
- Built-in rechargeable battery back-up
- Easy installation
- Test button to test strobe light
- Mains “Power On” and “Battery Low” fault indication
- Aesthetically pleasing design
- Intense 4.2 Joule white strobe light
- Unique anti-tamper mounting base
- 1 year Guarantee (limited)

### Product Description

Conventional Smoke Alarms are not effective in alerting those with hearing impairments, yet the early warning of a fire is no less important. This visual warning device can be interconnected with your Brooks smoke alarm. It has a rechargeable battery backup, and provides the necessary standby power so it can provide a warning even if the mains supply fails.

### Specifications

<b>Primary Supply:</b>	240V AC / 100mA Maximum
<b>Secondary Back-up Battery:</b>	12V / 0.7AH sealed lead acid battery
<b>Strobe:</b>	4.2 Joules, Flash rate of 90 per minute, clear colour
<b>Power ON Indication:</b>	Green LED
<b>Fault Indication:</b>	Yellow LED, steady illumination for battery low and flashing for battery fail
<b>Maximum number per system:</b>	Not limited, dependent on number of smoke/heat alarms fitted in the system
<b>Mounting:</b>	Plug in with anti-tamper base with option for flush or surface mounting
<b>Temperature Range:</b>	0°C to 40°C
<b>Humidity:</b>	15% to 95% Relative Humidity
<b>Material:</b>	Fire retardant high impact white plastic
<b>Dimensions:</b>	200mm diameter x 100mm H (including dome)
<b>Weight:</b>	950g (including battery)
<b>Approvals:</b>	Meets AS3000 requirements
<b>Compatibility</b>	
<b>Mains Power:</b>	3000 Series 140RC Series 160e Series

Specifications subject to change at discretion of INS LifeGuard.